Vehicle data sheet · Citroën

Citroën e-Berlingo K9 – Chilled goods

Chilled transport · Electric refrigeration



Brand	**Citroën**
Model	**e-Berlingo K9**

1,7 m³ / 2,1 m³
Load volume

1
Euro pallets

Product data: 03.11.2026

Conversion specification

Base vehicle: panel van, sliding door on the right, K9 platform, battery electric (BEV)

Delivery code: 009129E01

The Kerstner chilled goods conversion for the Citroën e-Berlingo combines the highest insulation performance with consistent practicality – developed and manufactured for everyday use in food and chilled goods transport.

The conversion achieves a K coefficient of 0.33 W/m²K and is classified as “heavily insulated” under ATP requirements. This is made possible by the seamless connection of all insulation elements – including at the sliding door – without gaps or thermal bridges.

The polyurethane insulation components are water-repellent, antibacterial and impact-resistant, and meet the requirements of the ATP and HACCP guidelines. The easy-to-clean surface reduces the effort required to maintain hygiene in day-to-day operation.

Thanks to its computer-optimised fit, the conversion provides a usable load volume of 1.7-2.1 m³ with unobstructed clearance between the wheel arches, suitable for loading Euro pallets.

Variants and load space

L1 wheelbase 2,785 mm battery electric (BEV)

approx. 1.7m3

Wheelbase	2,785 mm
Load compartment length	1,520 mm
Width between wheel arches	1,120 mm
Upper width	1,350 mm
Interior height	970 mm
Evaporator height	100 mm
Load volume	1,7 m³
Euro pallets	1
Compatible refrigeration units	CoolJet C106 EA

L2 wheelbase 2,975 mm battery electric (BEV)

approx. 2.1m3

Wheelbase	2,975 mm
Load compartment length	1,870 mm
Width between wheel arches	1,120 mm
Upper width	1,350 mm
Interior height	970 mm
Evaporator height	100 mm
Load volume	2,1 m³

Euro pallets	1
Compatible refrigeration units	CoolJet C106 EA

Refrigeration

Temperature range: on request

CoolJet C106 EA

Underfloor · Stationary refrigeration: optional

The CoolJet C106 EA is an electric underfloor refrigeration unit designed for fresh delivery, operating at 12 V. Installation beneath the vehicle preserves the free roof area.

Application: chilled goods transport

Type: underfloor unit

Refrigeration capacity: max. 944 W at 0 °C

Operating voltage: 12 V

Max. current draw: 45 A

Airflow: 480 m³/h

Refrigerant: R134a

Installation height: unchanged

Standard equipment

• Easyfit insulation (k=0.33)

• Electric refrigeration system for refrigeration while driving

• PU floor with water-retaining sill

• Aluminium impact protection (approx. 14 cm high) on the left, right (except sliding door) and front wall

• Horizontal half-round lashing rails above the wheel arches on the left and right

• Electric refrigeration system

• LED interior light + emergency release

Vehicle codes

Required codes

• PC17 – Full bulkhead without window

• PX13 – Right sliding door with solid panel

• Double-wing rear door without rear windows with 180° hinges – mandatory for standby refrigeration

• BQ01 – CanBus connection socket for converters

• For towbar/pre-installation – on request

• ePower Take-Off 400 V distribution box

Excluded codes

• PX35 – Glazed bulkhead

• Spare wheel

• Left sliding door

• GB23/GB33/GB38/GB43/GB44 – Load floor or lining

• AD3 – Roof loading hatch

• PB02 – Tailgate

• HMG – Construction site package

• J89 – Overload indicator

• Trek preparation

• 5L7 – Start-stop function or deactivation

Equipment and accessories

Required accessories

TÜV assessment / Stage II certificate of conformity (COC)

Required accessories · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Required for submission at registration Quantity: Default 1, Minimum 1 piece

Optional accessories

Aluminium floor panel, wheelbase 2,785 mm

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Aluminium floor panel, wheelbase 2,975 mm

Optional · Suitable for: L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Non-slip load floor mat, wheelbase 2,785 mm

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Non-slip load floor mat, wheelbase 2,975 mm

Optional · Suitable for: L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Shelf set I (1 height-adjustable shelf)

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Shelf set I (2 shelves one above the other, height-adjustable)

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

PVC strip curtain for the rear opening

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

PVC strip curtain for the sliding door

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Horizontal lashing rails at a custom height on the left and right, wheelbase 2,785 mm

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Horizontal lashing rails at a custom height on the left and right, wheelbase 2,975 mm

Optional · Suitable for: L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

ATP certificate FRAX

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Non-slip mat for shelf

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Telescopic load restraint bar, 1 piece

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Transsafe load restraint bar, universally usable in all Airline rails Quantity: Default 1, Minimum 1 piece

Telescopic load restraint bar package, 2 pieces

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Transsafe load restraint bar, universally usable in all Airline rails Quantity: Default 1, Minimum 1 piece

Lashing strap package (2 straps)

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Quantity: Default 1, Minimum 1 piece

Euroscan RX3 temperature recorder with 2 sensors (available DIN slot required)

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

The Euroscan RX3 is the proven solution for installation in the cab's DIN radio slot. It is ideal for vehicles requiring a compact, robust system with an integrated printer. DIN slot format — easy installation without requiring additional space. Thermal transfer printer — maintenance-free and directly accessible to the driver. Up to 6 analogue probes — reliable sensing for established applications. Optional ColdChainView — integration via an external module. Technical specifications: Installation format: DIN radio slot (cab). Analogue probes: up to 6. Digital inputs: 4. Interfaces: 2× RS-232 · 1× CAN · 1× digital output. Printer: thermal transfer (maintenance-free). Communication: GSM / GPS via an external module (optional). Protection rating: IP20. Dimensions: 186 × 58 × 150 mm. Operating temperature: –30 °C to +70 °C. Certification: EN 12830:2018 · GAMP5 · GDP · HACCP · CE.

Euroscan RT8 RX 4G LTE temperature recorder with 2 sensors (available DIN slot required)

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

DIN slot supplied by Kerstner if not fitted at the factory

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Position chosen at Kerstner's discretion according to available cab space

Stationary refrigeration 230 V

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Including external socket and 8m connecting cable

Warranty extension to 3 years

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Warranty extension from 24 to 36 months – according to our warranty terms –

Warranty extension to 4 years

Optional · Suitable for: L1 wheelbase 2,785 mm battery electric (BEV) / CoolJet C106 EA; L2 wheelbase 2,975 mm battery electric (BEV) / CoolJet C106 EA

Warranty extension from 24 to 48 months – according to our warranty terms –

Kerstner GmbH
Werner-von-Siemens-Straße 9
68649 Groß-Rohrheim

+49 6245 90770-0
info@kerstner.de
www.kerstner.de