Vehicle data sheet · Volkswagen

VW Crafter · Chilled transport with belt drive

Chilled transport · Belt drive



Brand	**Volkswagen**
Model	**Crafter fresh delivery belt drive**

9 m³ / 8,5 m³ / 11,5 m³ / 10,8 m³
Load volume

3
Euro pallets

Product data: 13.11.2026

Conversion specification

Base vehicle: panel van, front- or rear-wheel drive, sliding door on the right, internal combustion engine (ICE)

Delivery code: 00795

The Kerstner chilled goods conversion for the VW Crafter combines the highest insulation performance with consistent practicality – developed and manufactured for everyday use in food and chilled goods transport.

The conversion achieves a K coefficient of below 0.4 W/m²K and is classified as “heavily insulated” under ATP requirements. This is made possible by the seamless connection of all insulation elements – including at the sliding door – without gaps or thermal bridges.

The engine-driven refrigeration system reliably maintains the temperature range from 0 °C to +20 °C throughout the journey.

The polyurethane insulation components are water-repellent, antibacterial and impact-resistant, and meet the requirements of the ATP and HACCP guidelines. The easy-to-clean surface reduces the effort required to maintain hygiene in day-to-day operation.

Thanks to its computer-optimised fit, the conversion provides a usable load volume of 8.5 - 11.5 m³ with unobstructed clearance between the wheel arches, suitable for loading Euro pallets.

Variants and load space

L3H3 wheelbase 3,640 mm front-wheel drive

high roof

Wheelbase	3,640 mm
Load compartment length	3,057 mm
Width between wheel arches	1,240 mm
Upper width	1,620 mm
Interior height	1,785 mm
Evaporator height	100 mm
Load volume	9 m³
E2 crates	117
Euro pallets	3
Compatible refrigeration units	CoolJet C206RA / Thermo King V200 max 50 / Thermo King V200 max 20 / Thermo King V400X Max 20 / Thermo King V400X Max 50

L3H3 wheelbase 3,640 mm rear-wheel drive

high roof

Wheelbase	3,640 mm
Load compartment length	3,057 mm

Width between wheel arches	1,243 mm
Upper width	1,622 mm
Interior height	1,685 mm
Evaporator height	100 mm
Load volume	8,5 m³
E2 crates	105
Euro pallets	3
Compatible refrigeration units	CoolJet C206RA / Thermo King V200 max 50 / Thermo King V200 max 20 / Thermo King V400X Max 20 / Thermo King V400X Max 50

L4H3 wheelbase 4,490 mm front-wheel drive

high roof

Wheelbase	4,490 mm
Load compartment length	3,886 mm
Width between wheel arches	1,240 mm
Upper width	1,620 mm
Interior height	1,785 mm
Evaporator height	100 mm
Load volume	11,5 m³
E2 crates	120
Euro pallets	3
Compatible refrigeration units	CoolJet C206RA / Thermo King V200 max 50 / Thermo King V200 max 20 / Thermo King V400X Max 20 / Thermo King V400X Max 50

L4H3 wheelbase 4,490 mm rear-wheel drive

high roof

Wheelbase	4,490 mm
Load compartment length	3,886 mm
Width between wheel arches	1,243 mm
Upper width	1,622 mm
Interior height	1,685 mm
Evaporator height	1,143 mm
Load volume	10,8 m³
E2 crates	120
Euro pallets	3
Compatible refrigeration units	CoolJet C206RA / Thermo King V200 max 50 / Thermo King V200 max 20 / Thermo King V400X Max 20 / Thermo King V400X Max 50

Refrigeration

Temperature range: on request

CoolJet C206RA

Roof-mounted · Stationary refrigeration: optional

The CoolJet C206RA is a roof-mounted refrigeration unit with belt drive designed for fresh delivery.

Application: chilled goods transport

Type: roof-mounted unit

Refrigeration capacity: max. 3,157 W at 0 °C

Operating voltage: 12 V

Max. current draw: 24 A

Airflow: 1,120 m³/h

Refrigerant: R134a

Installation height: +250 mm

Thermo King V200 max 50

External · Stationary refrigeration: included

- Split refrigeration unit for installation on the front wall or roof

- Ultra-flat ES 200 evaporator with 2 fans, airflow 1,070 m³/h

- In-transit cooling at 12 V (driven by the vehicle engine) and 230 V electric motor

- Manual defrost or automatic timer-controlled defrost

- In-cab remote control with temperature display

The remote control and temperature recorder are installed in the existing

available DIN slot. Otherwise, they are installed at a location

we consider suitable. Subsequent changes can be made

and will be charged according to the work required.

- DSR controller – Smart Reefer

- Effective refrigeration capacity at an ambient temperature of 30 °C under ATP conditions:

2,710 W at 0 °C

1,560 W at -20 °C

1,190 W at -25 °C

- Heating capacity approx. 2,400 W

945 W at -20 °C

- R452A refrigerant: particularly environmentally friendly – 50% lower CO^2 impact; complies with legal requirements from 2020

Application: chilled and frozen goods transport

Type: roof-mounted

Cooling capacity: 2,710 W at 0 °C

Operating voltage: 12 V

Max. current draw: 452 A

Air flow: 1,070 m³/h

Refrigerant: R452A

Installation height: +221 mm

Note: & roof

Thermo King V200 max 20

External · Stationary refrigeration: included

- Split refrigeration unit for installation on the front wall or roof

- Ultra-flat ES 200 evaporator with 2 fans, airflow 1,070 m³/h

- In-transit cooling at 12 V (driven by the vehicle engine) and 230 V electric motor

- Manual defrost or automatic timer-controlled defrost

- In-cab remote control with temperature display

The remote control and temperature recorder are installed in the existing

available DIN slot. Otherwise, they are installed at a location

we consider suitable. Subsequent changes can be made

and will be charged according to the work required.

- DSR controller – Smart Reefer

- Effective refrigeration capacity at an ambient temperature of 30 °C under ATP conditions:

2,710 W at 0 °C

1,560 W at -20 °C

1,190 W at -25 °C

- R452A refrigerant: particularly environmentally friendly – 50% lower CO^2 impact; complies with legal requirements from 2020

Application: chilled and frozen goods transport

Type: roof-mounted

Cooling capacity: 2,710 W at 0 °C

Operating voltage: 12 V

Max. current draw: 452 A

Air flow: 1,070 m³/h

Refrigerant: R452A

Installation height: +221 mm

Note: & roof

Thermo King V400X Max 20

Roof-mounted · Stationary refrigeration: included

Thermo King V-400X MAX: powerful and quiet refrigeration unit without its own engine and without exhaust emissions. The temperature is precisely regulated to 1 °C, with standby cooling possible via mains power

The Thermo King V-400X MAX from the VX series offers high cooling capacity and precise temperature control. Using the control panel in the driver's cab, you regulate the load space temperature in single and multi-temperature operation to an accuracy of 1 °C.

Since the unit operates without its own motor, it produces no emissions and runs particularly quietly. This is an advantage for deliveries in city centers and residential areas.

The device weighs only 75 kg (model 50) and is compactly built, leaving more payload capacity for the cargo. The aerodynamic design is optimized for daily use.

- Cooling capacity during driving: 4.082 W at 0 °C / 2.237 W at -20 °C

- Cooling capacity during mains operation: 3.026 W at 0 °C / 1.496 W at -20 °C

- Airflow volume: 1.990 m³/h

- Temperature control: Single and multi-temperature, accurate to 1 °C

- Operation: Operating panel inside the driver's cab

Application: Fresh delivery and deep-freeze

Type: roof-mounted unit

Cooling capacity: 4082 watts

Operating voltage: 12 V

Max. current draw: 452 A

Air flow: 1990m³

Refrigerant: R452a

Installation height: +273 mm

Note: driving and standby refrigeration

Thermo King V400X Max 50

Roof-mounted · Stationary refrigeration: included

The V-400X MAX from Thermo King's VX series is powered by the vehicle's engine and requires no separate motor. This ensures quiet operation with minimal vibrations and no exhaust emissions, making it ideal for deliveries in city centers and low-emission zones, including at night.

With a cooling capacity of 4.082 W at 0 °C and 2.240 W at –20 °C, this unit is suitable for both fresh delivery and deep-freeze transport. The cab controller Direct Smart Reefer (DSR III) maintains the cargo area temperature within ±1 °C. It displays malfunctions via clear alarm codes and automatically reminds of scheduled maintenance.

The 50 version offers two additional features: through electric standby, the unit continues cooling when the engine is off using an external power supply at 400 V. The heating function protects the cargo in winter from excessively low temperatures.

The lightweight, aerodynamic housing preserves payload capacity. The condenser can be mounted on the front wall, on the roof, or recessed into the roof. Defrosting is automatic via hot gas.

Optional equipment includes door switches, a DIN adapter for installing the controller in the radio slot, telematics via BlueBox Lite, and data loggers compliant with EN 12830. The max 50 version offers: cooling during transit, cooling while stationary via external 400 V power connection, as well as a heating function with 3.564 W during driving operation, and 1,841 W during mains operation.

Application area: fresh delivery / deep-freeze

Type: roof-mounted unit

Cooling capacity: 4.082 W during transit

Operating voltage: 12 V

Maximum current: 36 A

Air flow: 1.990 m³/h

Refrigerant: R452a

Unit height: +273 mm

Standard equipment

• Kerstner easyfit insulation (k=0.33)

• Refrigeration system for refrigeration while driving

• Smooth polyester floor

• Aluminium impact protection (approx. 20 cm high) on the left, right (except sliding door) and front wall

• Horizontal half-round lashing rails at approx. 40cm height on the right and left above the wheel arches

• LED interior light

• 2x emergency release

• Water-retaining sill in the sliding door area

• 2 front water drains

Vehicle codes

Required codes

• 3RD 631WA – Rear wing door without window cutouts – standard

• 3CF 637BC – Bulkhead without window – standard

• IS2 631JD – Electrical terminal strip and KFG function control unit 1 with ABH programme

• 5R5 635TD – Right sliding door, special version with increased outward travel and hold-open device, or

• 5R6 635TE – Right sliding door, special version with increased outward travel without hold-open device

• 3SJ 634RG – Right double passenger bench seat with storage compartment

• 9CX 632DE – Preparation for cargo space lighting or

• 9CW 632D – LED interior lighting system in passenger/load compartment

• 2A7 634JB – Transport mode deactivation MY2024/2025

• 2AB 632IL – Refrigerant compressor installation (factory-fitted)

• 5V4 634HC – Hinges for rear wing doors with enlarged opening angle – recommended

• QT4 631DR – With step at rear across entire width – recommended / not for tail lift

• 6B0 637MA – Without lashing eyes for load securing – recommended

• QE1 630EL – DIN slot – mandatory for temperature recorder

Excluded codes

• IG2 633YB – Steel spare wheel – for underfloor C206EA

Equipment and accessories

Required accessories

TÜV assessment / Stage II certificate of conformity (COC)

Required accessories · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King

V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Required for submission at registration Quantity: Default 1, Minimum 1 piece

Optional accessories

EBERSPÄCHER auxiliary heater for load compartment

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Aluminium chequer-plate floor panel RA 3640

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Aluminium chequer-plate floor panel RA 4490

Optional · Suitable for: L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Surcharge for twin wheels

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Non-slip load floor mat RA 3640

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Non-slip load floor mat RA 4490

Optional · Suitable for: L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Non-slip mat for shelving

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Shelf set I (1x shelf, 4x lashing rails)

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Shelf set II (2x shelves, 4x lashing rails, fitted one above the other)

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Additional lashing rail set for fitting shelves one behind the other

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Per additional shelf

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490

mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Additional LED load compartment light

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Multi-compartment solution, fixed partition ahead of wheel arches

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

PVC strip curtain for the rear opening

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive /

Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

PVC strip curtain for the sliding door

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Additional lashing rails at a custom height of 40-120cm RA 3640

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Additional lashing rails at a custom height of 40-120cm RA 4490

Optional · Suitable for: L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

ATP FRAX

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Partition in load compartment for multi-compartment solution

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Increased door-closing forces: Installing a partition increases the force required to close the doors and can lead to increased sliding-door wear over time. Please also note: If a fixed multi-compartment partition without a passage is installed in the load compartment, the German employers' liability insurance association (BG) rules require a step at the sliding door, because the partition removes access to the front compartment through the rear doors. According to the BG, the customer may not enter the front compartment without a step and may only load and unload it from outside. Quantity: Default 1, Minimum 1 piece

Shelf system I: Crosswise wire mesh shelf 1 level

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Wire mesh shelf spanning the entire vehicle width, from rear portal to sliding door. Removable, not height-adjustable. Position: approx. 700 mm height Quantity: Specification 1, Minimum 1 pieces

Additional Floor at 1.200 mm Height

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Shelf System II: Wire Mesh Shelf Crosswise with 2 Levels

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3

wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

2 wire mesh shelves spanning the entire vehicle width, from rear portal to sliding door. Removable, not height-adjustable. Position: approx. 700 mm and 1,200 mm height (adapted per model) Quantity: Specification 1, Minimum 1 pieces

Wheel arch cover top, right and left

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Side paneling right, left, and front wall up to 700 mm height

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Aluminum smooth sheet dimensions may vary depending on the model Quantity: Standard 1, minimum 1 pieces

Side paneling right, left, and front wall up to 1,200 mm height

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Aluminum smooth sheet dimensions may vary depending on the model Quantity: Standard 1, minimum 1 pieces

Bär VanLift FreeAccess A2V MAN/Crafter version

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Platform dimensions 1,110 mm (height) x 1,330 mm*** (width) Load capacity: 500 kg Load distance: 600 mm Vertically folded platform, parked behind the left rear door Bär SmartControl Basic handheld remote control Included divided VanBridge, creating a seamless transition between platform and loading floor via an unloaded rubber hinge. Slip-resistant thanks to ribbed surface. Can be locked vertically in the cargo area during travel Included divided roll-off protection for roll containers, opening angle approx. 90 degrees Included foot switch unit, LED warning lights, warning flags, license plate light and number plate lights on the platform, driver’s cab activation Included platform rear powder-coated in RAL 9006 White Aluminium. Edge trim profile anodized Included 2 years warranty Exclusion code for this option: QT9 – Rear step, half width (for L3H3 wheelbase 3,640 mm front-wheel drive, L3H3 wheelbase 3,640 mm rear-wheel drive, L4H3 wheelbase 4,490 mm front-wheel drive, L4H3 wheelbase 4,490 mm rear-wheel drive) Exclusion code for this option: QT4 – Rear step, full width (for L3H3 wheelbase 3,640 mm front-wheel drive, L3H3 wheelbase 3,640 mm rear-wheel drive, L4H3 wheelbase 4,490 mm front-wheel drive, L4H3 wheelbase 4,490 mm rear-wheel drive) Quantity: preset 1, minimum 1 piece

Emergency operation

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Detachable towball coupling complete with ball, D-value 21 kN

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Telescopic load restraint bar, 1 piece

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Transsafe load restraint bar, universally usable in all Airline rails Quantity: Default 1, Minimum 1 piece

Telescopic load restraint bar package, 2 pieces

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Transsafe load restraint bar, universally usable in all Airline rails Quantity: Default 1, Minimum 1 piece

Lashing strap package (2 straps)

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Quantity: Default 1, Minimum 1 piece

Euroscan RX3 temperature recorder with 2 sensors (available DIN slot required)

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA

The Euroscan RX3 is the proven solution for installation in the cab’s DIN radio slot. It is ideal for vehicles requiring a compact, robust system with an integrated printer. DIN slot format — easy installation without requiring additional space. Thermal transfer printer — maintenance-free and directly accessible to the driver. Up to 6 analogue probes — reliable sensing for established applications. Optional ColdChainView — integration via an external module. Technical specifications: Installation format: DIN radio slot (cab). Analogue probes: up to 6. Digital inputs: 4. Interfaces: 2× RS-

232 · 1× CAN · 1× digital output. Printer: thermal transfer (maintenance-free). Communication: GSM / GPS via an external module (optional). Protection rating: IP20. Dimensions: 186 × 58 × 150 mm. Operating temperature: –30 °C to +70 °C. Certification: EN 12830:2018 · GAMP5 · GDP · HACCP · CE.

Euroscan RT8 RX 4G LTE temperature recorder with 2 sensors (available DIN slot required)

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA

DIN slot supplied by Kerstner if not fitted at the factory

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X max 50

Position chosen at Kerstner’s discretion according to available cab space

Thermo King Touchlog Premium temperature recorder

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X Max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X Max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X Max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X Max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X Max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X Max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X Max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X Max 50

Blue Box Lite including installation

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X Max 20; L3H3 wheelbase 3,640 mm front-wheel drive / Thermo King V400X Max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 50; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V200 max 20; L3H3 wheelbase 3,640 mm rear-wheel drive / Thermo King V400X Max 20; L3H3 wheelbase 3,640 mm rear-

wheel drive / Thermo King V400X Max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X Max 20; L4H3 wheelbase 4,490 mm front-wheel drive / Thermo King V400X Max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 50; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V200 max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X Max 20; L4H3 wheelbase 4,490 mm rear-wheel drive / Thermo King V400X Max 50

Refrigeration unit cover painted in vehicle colour – solid –

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA

Refrigeration unit cover painted in vehicle colour – metallic –

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA

230 V standby cooling, chilled transport variant

Optional · Suitable for: L3H3 wheelbase 3,640 mm front-wheel drive / CoolJet C206RA; L3H3 wheelbase 3,640 mm rear-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm front-wheel drive / CoolJet C206RA; L4H3 wheelbase 4,490 mm rear-wheel drive / CoolJet C206RA

Including external socket and 8m connecting cable

Kerstner GmbH
Werner-von-Siemens-Straße 9
68649 Groß-Rohrheim

+49 6245 90770-0
info@kerstner.de
www.kerstner.de